


MSZ-WX24NL & MUZ-WX24NL
22,400 BTU/H WALL-MOUNTED INDOOR UNIT
22,400 BTU/H INVERTER HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... MSZ-WX24NL

OUTDOOR Unit ... MUZ-WX24NL

INDOOR UNIT FEATURES

- Econo Cool: Econo Cool is feature that temporarily adjusts the airflow to maintain comfort while using less energy.
- Smart Dry Mode: Improves humidity control with minimal over-cooling of the space.
- Swing Mode: An indoor unit with this capability can move air throughout the room like an oscillating fan.
- Nano Platinum Filter: This filter has a large capture area and incorporates nanometer-sized platinum-ceramic particles and is designed to reduce the presence of certain nonliving particles, while deodorizing the circulating air.
- Horizontal Vane Control: Horizontal Vane Control allows the indoor unit vanes to be moved left right to provide even temperatures throughout a space.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: Designed to protect against the corrosive effects of environments that are in close proximity to the sea.

SPECIFICATIONS: MSZ-WX24NL & MUZ-WX24NL

Cooling at 95F ¹	Maximum Capacity	Btu/h	22400
	Rated Capacity	Btu/h	22400
	Minimum Capacity	Btu/h	5800
	Maximum Power Input	W	2800
	Rated Power Input	W	2800
	Moisture Removal	Pints/h	6.10
	Sensible Heat Factor		0.70
	Power Factor [208V / 230V]	%	98 / 98
Heating at 47F ²	Maximum Capacity	Btu/h	26000
	Rated Capacity	Btu/h	26000
	Minimum Capacity	Btu/h	5400
	Maximum Power Input	W	2680
	Rated Power Input	W	2680
	Power Factor [208V / 230V]	%	97 / 97
Heating at 17F ³	Maximum Capacity	Btu/h	17800
	Rated Capacity	Btu/h	17000
	Maximum Power Input	W	2300
	Rated Power Input	W	2100
Heating at 5F ⁵	Maximum Capacity	Btu/h	14490
	Maximum Power Input	W	2150
Efficiency	SEER2		18
	EER2 ¹		8
	HSPF2 [IV]		8.50
	COP at 47°F ²		2.84
	COP at 17°F at Maximum Capacity ³		2.26
	COP at 5°F at Maximum Capacity ⁵		1.97
	ENERGY STAR® Certified		No
Electrical	Voltage, Phase, Frequency	V AC / V AC , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	187 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	230 / 208
	Voltage: Indoor - Outdoor, S2-S3	V DC	24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	20
	Recommended Wire Size [Indoor - Outdoor]	AWG	14
	MCA	A	1
Indoor Unit	Fan Motor Output	W	40
	Fan Motor Type		DC Motor
	Airflow Rate at Cooling, Dry	CFM	322 , 427 , 527 , 622
	Airflow Rate at Cooling, Wet	CFM	290 , 384 , 474 , 560
	Airflow Rate at Heating, Dry	CFM	335 , 446 , 574 , 698
	Sound Pressure Level [Cooling]	dB (A)	33 , 38 , 44 , 50
	Sound Pressure Level [Heating]	dB (A)	32 , 38 , 44 , 50
	Drain Pipe Size O.D.	inch [mm]	5/8 [15.88]
	Dual Barrier Coating on Heat Exchanger		No
	Dual Barrier Coating on Fan		No
	External Finish Color		Munsell 0.7PB 9.2/0.4
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	36-5/16 x 10-5/16 x 12 [923 x 263 x 305]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	39-1/2 x 15-1/4 x 13-1/4 [1000 x 390 x 350]
	Unit Weight	lbs [kg]	28 [12.40]
	Package Weight	lbs [kg]	32 [14.50]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	deg F , deg F / deg F , deg F	90 , 73 / 67 , 57
	Heating Intake Air Temp [Maximum / Minimum]	deg F	80 / 70
Outdoor Unit	MCA	A	16
	MOCP	A	20
	Fan Motor Full Load Amperage	A	0.74

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

⁴Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB. Not AHR1 rated

^{*}Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

^{*}Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.

³Nominal capacity only. Actual capacity output varies based on the system specific configuration

SPECIFICATIONS: MSZ-WX24NL & MUZ-WX24NL

Outdoor Unit	Fan Motor Output	W	55
	Airflow Rate Cooling	CFM	1816
	Airflow Rate Heating	CFM	1582
	Defrost Method		Reverse Cycle
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling ¹	dB (A)	57
	Sound Pressure Level, Heating ²	dB (A)	55
	Compressor Type		Twin Rotary
	Compressor Model		SRB140FQHMT
	Compressor Oil [Type // Charge]	// oz	RM68EH // 11.83
	External Finish Color		Munsell 3Y 7.8/1.1
	Base Pan Heater		Optional
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	31-1/2 x 11-1/4 x 28-1/8 [800 x 285 x 714]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	39-1/2 x 15-1/4 x 13-1/2 [1000 x 390 x 350]
ODU Operating Temp. Range	Unit Weight	lbs [kg]	90 [40.8]
	Package Weight	lbs [kg]	104 [47.2]
	Cooling Intake Air Temp [Maximum / Minimum*]	F	115 / 32
	Cooling Thermal Lock-out / Re-start Temperatures**	F	-1 / 3
Refrigerant	Heating Intake Air Temp [Maximum / Minimum]	F , F / F , F	75 , 65 / 5 , 4
	Heating Thermal Lock-out / Re-start Temperatures**	F	-14 / -4
	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	2 , 8
Piping	Maximum Pre-Charged Piping Length	ft [m]	25 [7.50]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.22
	Gas Pipe Size O.D. [Flared]	inch [mm]	1/2 [12.72]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	1/4 [6.35]
Piping	Maximum Piping Length	ft [m]	65 [20]
	Maximum Height Difference	ft [m]	40 [12]
	Maximum Number of Bends		10

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

⁴Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB. Not AHRI rated

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.

³Nominal capacity only. Actual capacity output varies based on the system specific configuration

INDOOR UNIT ACCESSORIES: MSZ-WX24NL


Condensate	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	☐ X87-711
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Refco Condensate Removal Pump with Wall Mount Enclosure 120-240V up to 120k BTU/h	☐ GOBI-II
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
	Blue Diamond Advanced Mini Condensate Pump w Reservoir Sensor 208230V recommended	☐ X88-721
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Drain Pan Level Sensor/Control	☐ SS610E
Control Interface	IT Extender	☐ PAC-WHS01IE-E
	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	Wireless Interface 2 for Comfrot app	☐ PAC-USWHS002-WF-2
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	M-Net I/O Control Interface for M-Series ²	☐ MAC-334IF-E
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black (30A/600V/UL) [fits 2" X 4" utility box] - White	☐ TAZ-MS303 ☐ TAZ-MS303W
Drain Hose	Flexible Mini-Split Drain Hose	☐ DRX-16
Filter	Electro Static Anti-allergy Enzyme Filter	☐ MAC-2320FT-E
	Microparticle Filter	☐ MAC-EMF515FT-E
Lineset	1/4 x 1/2 Lineset Twin-Tube Insulation - 30 feet	☐ MLS141212T-30
	1/4 x 1/2 Lineset Twin-Tube Insulation - 15 feet	☐ MLS141212T-15
	1/4 x 1/2 Lineset Twin-Tube Insulation - 50 feet	☐ MLS141212T-50
	1/4 x 1/2 Lineset Twin-Tube Insulation - 65 feet	☐ MLS141212T-65
	1/4 x 1/2 Lineset Twin-Tube Insulation - 100 feet	☐ MLS141212T-100
Remote Sensor	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
Terminal Signal Adapter	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Simple MA Remote Controller ¹	☐ PAC-YT53CRAU-J
	Touch MA Remote Controller ¹	☐ PAR-CT01MAU-SB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Deluxe MA Wired Remote Controller ¹	☐ PAR-42MAAUB
Wireless Remote Controller	Wireless RedLINK™ Remote Controller	☐ MHK2
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
Notes		

OUTDOOR UNIT ACCESSORIES: MUZ-WX24NL

Air Outlet Guide	Air Outlet Guide	☐	MAC-890SG-E
Control/Service Tool	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
	Maintenance Tool Interface	☐	PAC-USCMS-MN-1
Drain Socket	Drain Socket	☐	MAC-871DS
Mini-Split Wire	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	16 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S164-250
	16 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW164-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
	16 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S164-50
	16 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW164-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
Mounting Pad	Condensing Unit Mounting Pad 16 x 36 x 3	☐	ULTRILITE1
Optional Defrost Heater	Base Heater	☐	MAC-650BH-U
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-1
Stand	Outdoor Unit Stand 12 High	☐	QSMS1201M
	18 Single Fan Stand	☐	QSMS1801M
	24 Single Fan Stand	☐	QSMS2401M
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
	Condenser Wall Bracket	☐	QSWB2000M-1
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
Notes			

INDOOR UNIT DIMENSIONS: MSZ-WX24NL

MSZ-WX24NL - U1



MUZ-WX24NL-U1



© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.