

PKA-AL18NL & PUZ-AK18NL
18,000 BTU/H WALL-MOUNTED INDOOR UNIT
18,000 BTU/H HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... PKA-AL18NL
OUTDOOR Unit ... PUZ-AK18NL

INDOOR UNIT FEATURES

- Auto Vane Control: Auto Vane Control allows the indoor unit vanes to be moved left, right, up, and down to provide even temperatures throughout a space.
- Swing Mode: An indoor unit with this capability can move air throughout the room like an oscillating fan.
- Light Commercial: Light commercial applications include small offices, restaurants, and retail.
- Horizontal Vane Control: Horizontal Vane Control allows the indoor unit vanes to be moved left right to provide even temperatures throughout a space.
- Four Speed Fan: Adjust the fan between four speed settings to optimal comfort.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: Designed to protect against the corrosive effects of environments that are in close proximity to the sea.

SPECIFICATIONS: PKA-AL18NL & PUZ-AK18NL

Cooling at 95F ¹	Maximum Capacity	Btu/h	18000
	Rated Capacity	Btu/h	18000
	Minimum Capacity	Btu/h	4300
	Maximum Power Input	W	1630
	Rated Power Input	W	1630
	Moisture Removal	Pints/h	6.60
	Sensible Heat Factor		0.60
	Power Factor [208V / 230V]	%	93 / 93
Heating at 47F ²	Maximum Capacity	Btu/h	23600
	Rated Capacity	Btu/h	22000
	Minimum Capacity	Btu/h	4200
	Maximum Power Input	W	2300
	Rated Power Input	W	2079
	Power Factor [208V / 230V]	%	91 / 91
Heating at 17F ³	Maximum Capacity	Btu/h	11700
	Rated Capacity	Btu/h	11700
	Maximum Power Input	W	1410
	Rated Power Input	W	1410
Heating at 5F ⁵	Maximum Capacity	Btu/h	9200
	Maximum Power Input	W	1340
Heating at -4F ⁶	Maximum Capacity	Btu/h	8900
Efficiency	SEER2		19.50
	EER2 ¹		11
	HSPF2 [IV]		8.90
	COP at 47°F ²		3.10
	COP at 17°F at Maximum Capacity ³		2.40
	COP at 5°F at Maximum Capacity ⁵		2
	COP at -4°F at Maximum Capacity ⁶		2.04
	ENERGY STAR® Certified		Yes
Electrical	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	20
	Recommended Wire Size [Indoor - Outdoor]	AWG	14
Indoor Unit	Fan Motor Output	W	30
	Fan Motor Type		DC Motor
	Airflow Rate at Cooling, Dry	CFM	265 , 310 , 375 , 450
	Airflow Rate at Cooling, Wet	CFM	215 , 255 , 320 , 375
	Airflow Rate at Heating, Dry	CFM	265 , 310 , 375 , 450
	Sound Pressure Level [Cooling]	dB (A)	34 , 39 , 44 , 48
	Sound Pressure Level [Heating]	dB (A)	34 , 39 , 44 , 48
	External Static Pressure	in.WG	
	Dual Barrier Coating on Fan		No
	External Finish Color		0.7PB 9.2/0.4
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	35-11/32 x 9-11/32 x 11-25/32 [898 x 237 x 299]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	38-1/4 x 13-7/16 x 14-3/16 [970 x 340 x 360]
	Unit Weight	lbs [kg]	28 [12.70]
	Package Weight	lbs [kg]	32 [14.50]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	deg F , deg F / deg F , deg F	90 , 73 / 66 , 59
	Heating Intake Air Temp [Maximum / Minimum]	deg F	82 / 50
Outdoor Unit	MCA	A	16
	MOCP	A	27
	Fan Motor Full Load Amperage	A	

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB - test

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

⁵Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Heat pump system with wind baffle: 0°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.

⁶Heating at -4°F (Indoor // Outdoor) °F 70 DB, 60 WB // -4 DB, -5 WB

SPECIFICATIONS: PKA-AL18NL & PUZ-AK18NL

Outdoor Unit	Fan Motor Output	W	51
	Airflow Rate Cooling	CFM	1590
	Airflow Rate Heating	CFM	1590
	Defrost Method		Reverse Cycle
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling ¹	dB (A)	44
	Sound Pressure Level, Heating ²	dB (A)	46
	Compressor Type		Twin Rotary
	Compressor Model		SRB140FQHMC-L1
	Compressor Oil [Type // Charge]	// oz	RM68EH // 16
	External Finish Color		Munsell 3Y 7.8/1.1
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	34-19/64 x 11-13/16 x 24-13/16 [871 x 300 x 630]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	37-1/16 x 16-3/16 x 32-1/4 [941 x 411 x 819]
ODU Operating Temp. Range	Unit Weight	lbs [kg]	99.21 [45]
	Package Weight	lbs [kg]	112 [51]
	Cooling Intake Air Temp [Maximum / Minimum*]	F	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	F	
Refrigerant	Heating Intake Air Temp [Maximum / Minimum]	F , F / F , F	70 , 59 / -4 , -4
	Heating Thermal Lock-out / Re-start Temperatures**	F	-13 / -4
	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	4 , 6
Piping	Maximum Pre-Charged Piping Length	ft [m]	100 [30]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0
	Gas Pipe Size O.D. [Flared]	inch [mm]	1/2 [12.7]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	1/4 [6.35]
Piping	Maximum Piping Length	ft [m]	100 [30]
	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB - test

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

⁵Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Heat pump system with wind baffle: 0°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.

⁶Heating at -4°F (Indoor // Outdoor) °F 70 DB, 60 WB // -4 DB, -5 WB


INDOOR UNIT ACCESSORIES: PKA-AL18NL

Condensate	Blue Diamond MicroBlue Condensate Pump with Fascia Kit 115-230V up to 18k BTU/h	☐ X86-011
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
	Refco Condensate Removal Pump with Wall Mount Enclosure 120-240V up to 120k BTU/h	☐ GOBI-II
	Drain Pan Level Sensor/Control	☐ SS610E
	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	☐ X87-711
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Blue Diamond MicroBlue Mini Condensate Pump 110208230V up to 18000 BTUH	☐ X85-003
Control Interface	Wireless Interface 2 for Comfort app	☐ PAC-USWHS002-WF-2
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	IT Extender	☐ PAC-WHS01IE-E
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
	(30A/600V/UL) [fits 2" X 4" utility box] - White	☐ TAZ-MS303W
Drain Hose	Flexible Mini-Split Drain Hose	☐ DRX-16
Lineset	1/4 x 1/2 Lineset Twin-Tube Insulation - 15 feet	☐ MLS141212T-15
	1/4 x 1/2 Lineset Twin-Tube Insulation - 65 feet	☐ MLS141212T-65
	1/4 x 1/2 Lineset Twin-Tube Insulation - 100 feet	☐ MLS141212T-100
	1/4 x 1/2 Lineset Twin-Tube Insulation - 30 feet	☐ MLS141212T-30
	1/4 x 1/2 Lineset Twin-Tube Insulation - 50 feet	☐ MLS141212T-50
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐ SW144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐ SW144-250
N/A		☐ Unknown
Remote Sensor	Wall Mounted Remote Temperature Sensor	☐ PAC-SE41TS-E
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	☐ PAC-USSEN002-FM-1
	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
Terminal Signal Adapter	3-Pin Wiring Harness	☐ PAC-715AD
	5-Pin Wiring Harness	☐ PAC-725AD
	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Touch MA Remote Controller	☐ PAR-CT01MAU-SB
	Deluxe MA Wired Remote Controller	☐ PAR-42MAAUB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Simple MA Remote Controller	☐ PAC-YT53CRAU-J
Wireless Remote Controller	Wireless MA Handheld Remote Controller (requires PAR-FA32MA-E)	☐ PAR-FL32MA-E
	Wireless RedLINK™ Remote Controller	☐ MHK2
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
	Wireless Remote Contoller	☐ PAR-SL101A-E
Notes		

OUTDOOR UNIT ACCESSORIES: PUZ-AK18NL

Air Outlet Guide	Air Outlet Guide	☐	PAC-SJ07SG-E
Centralized Drain Pan	Centralized Drain Pan	☐	PAC-SG63DP-E
Control/Service Tool	Maintenance Tool Interface	☐	PAC-USCMS-MN-1
	ControlService Tool	☐	PAC-SK52ST
	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
Drain Socket	Drain Socket	☐	MAC-871DS
Hail Guards	Hail Guard	☐	HG-A5
M-NET Converter	M-Net Interface for P-Series	☐	PAC-SJ96MA-E
Mini-Split Wire	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
Mounting Pad	Condensing Unit Mounting Pad 16 x 36 x 3	☐	ULTRILITE1
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-2
Stand	Outdoor Unit Stand 12 High	☐	QSMS1201M
	Condenser Wall Bracket	☐	QSWB2000M-1
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
	24 Single Fan Stand	☐	QSMS2401M
	18 Single Fan Stand	☐	QSMS1801M
Terminal Signal Adapter	3-Pin Wiring Harness	☐	PAC-715AD
	5-Pin Wiring Harness	☐	PAC-725AD
Wind Baffle	Rear Wind Baffle	☐	WB-RE4
	Side Advanced Wind Baffle	☐	WB-SD4
	Front Wind Baffle	☐	WB-PA4
Notes			

INDOOR UNIT DIMENSIONS: PKA-AL18NL



METUS_2026-04_PROPIN

