


SEZ-AD18NL & SUZ-AA18NLHZ
18,000 BTU/H LOW STATIC HORIZONTAL-DUCTED INDOOR UNIT
16,400 BTU/H HYPER HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... SEZ-AD18NL

OUTDOOR Unit ... SUZ-AA18NLHZ

INDOOR UNIT FEATURES

- Wi-Fi Optional: A Wireless Interface Adapter can be ordered as an accessory for field installation.
- Three Speed Fan: Adjust the fan between three speed settings to optimal comfort.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.
- Light Commercial: Light commercial applications include small offices, restaurants, and retail.
- Condensate Lift Mechanism: Reduces the need for an additional pump to remove condensate. Units with a condensate lift mechanism also include an overflow safety switch.

OUTDOOR UNIT FEATURES

- H2i® Hyper-Heating: 100% heating capacity down to 5° F .
- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Base Pan Heater: This advanced base pan heater helps to prevent interrupted operation due to water freezing after a defrost cycle, ensuring your warmth and comfort during colder weather.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.

SPECIFICATIONS: SEZ-AD18NL & SUZ-AA18NLHZ

Cooling at 95F ¹	Maximum Capacity	Btu/h	18000
	Rated Capacity	Btu/h	18000
	Minimum Capacity	Btu/h	5500
	Maximum Power Input	W	1400
	Rated Power Input	W	1400
	Moisture Removal	Pints/h	4
	Sensible Heat Factor		0.75
Heating at 47F ²	Power Factor [208V / 230V]	%	97 / 97
	Maximum Capacity	Btu/h	23500
	Rated Capacity	Btu/h	20000
	Minimum Capacity	Btu/h	8400
	Maximum Power Input	W	1910
	Rated Power Input	W	1510
Heating at 17F ³	Power Factor [208V / 230V]	%	97 / 97
	Maximum Capacity	Btu/h	20000
	Rated Capacity	Btu/h	13100
	Maximum Power Input	W	2610
Heating at 5F ⁵	Rated Power Input	W	1370
	Maximum Capacity	Btu/h	20000
Heating at -13F ⁹	Maximum Power Input	W	2790
	Maximum Capacity	Btu/h	12100
Efficiency	SEER2		17
	EER2 ¹		12.80
	HSPF2 [IV]		10
	COP at 47°F ²		3.80
	COP at 17°F at Maximum Capacity ³		2.24
	COP at 5°F at Maximum Capacity ⁵		2.10
	COP at -13°F at Maximum Capacity ⁹		1.58
Electrical	ENERGY STAR® Certified		No
	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	30
Indoor Unit	Recommended Wire Size [Indoor - Outdoor]	AWG	14
	MCA	A	1.38
	MOCP	A	15
	Fan Motor Output	W	96
	Fan Motor Type		DC Motor
	Airflow Rate at Cooling, Dry	CFM	423 , 529 , 635
	Airflow Rate at Heating, Dry	CFM	423 , 529 , 635
	Sound Pressure Level [Cooling]	dB (A)	30 , 34 , 38
	Sound Pressure Level [Heating]	dB (A)	30 , 34 , 38
	External Static Pressure	in.WG	0.02 , 0.06 , 0.14 , 0.20
	Drain Pipe Size O.D.	inch [mm]	1-1/4 [32]
	Dual Barrier Coating on Heat Exchanger		No
	Dual Barrier Coating on Fan		No
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	46-7/8 x 27-9/16 x 7-7/8 [1190 x 700 x 200]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	55-1/8 x 35-7/16 x 14-3/16 [1400 x 900 x 360]
	Unit Weight	lbs [kg]	60 [27]
	Package Weight	lbs [kg]	84 [38]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB , °FWB / °FDB , °FWB	90 , 73 / 66 , 59
	Heating Intake Air Temp [Maximum / Minimum]	°FDB	83 / 50
Outdoor Unit	MCA	A	25

Notes

¹Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

⁵Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB

⁹Heating at -13°F (Indoor // Outdoor) °F 70 DB, 60 WB // -13 DB, -14 WB

^{*}Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

^{**}Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.

SPECIFICATIONS: SEZ-AD18NL & SUZ-AA18NLHZ

Outdoor Unit	MOCP	A	42
	Fan Motor Output	W	50
	Airflow Rate Cooling	CFM	2193
	Airflow Rate Heating	CFM	1949
	Defrost Method		Reverse Cycle
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes
	Sound Pressure Level, Cooling ¹	dB (A)	54
	Sound Pressure Level, Heating ²	dB (A)	55
	Compressor Type		Twin Rotary
	Compressor Model		SRB172FQHMT
	Compressor Oil [Type // Charge]	// oz	RM68EH // 14.5
	External Finish Color		Munsell No.3Y 7.8/1.1
	Base Pan Heater		Built-in
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	33-1/16 x 13 x 34-5/8 [840 x 330 x 880]
ODU Operating Temp. Range	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	38-5/8 x 16-9/16 x 39 [980 x 420 x 990]
	Unit Weight	lbs [kg]	115 [52.2]
	Package Weight	lbs [kg]	133 [60.3]
	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 14
Refrigerant	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	-1 / 3
	Heating Intake Air Temp [Maximum / Minimum]	°FDB , °FWB / °FDB , °FWB	70 , 65 / -13 , -14
	Heating Thermal Lock-out / Re-start Temperatures**	°FDB	-22.5 / -14
	Type		R454B
Piping	Pre-Charged Refrigerant Amount	lbs	3
	Maximum Pre-Charged Piping Length	ft [m]	25 [7.6]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.22
	Gas Pipe Size O.D. [Flared]	inch [mm]	1/2 [12.7]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	1/4 [6.35]
	Maximum Piping Length	ft [m]	100 [30]
	Maximum Height Difference	ft [m]	50 [15]
		inch [mm]	21-21/32 [550]
Notes ¹ Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB ² Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB ³ Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB ⁵ Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB ⁹ Heating at -13°F (Indoor // Outdoor) °F 70 DB, 60 WB // -13 DB, -14 WB *Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions. **Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures): • System cuts out in heating mode and automatically restarts at these temperatures.			

INDOOR UNIT ACCESSORIES: SEZ-AD18NL

Condensate	Blue Diamond Advanced Mini Condensate Pump w Reservoir Sensor 208230V recommended	☐ X88-721
	Blue Diamond MultiTank — collection tank for use with multiple pumps	☐ C21-014
	Refco Condensate Pump 100-240 VAC up to 120000 BTUH	☐ COMBI
	Blue Diamond MaxiBlue Advanced Mini Condensate Pump w Reservoir Sensor 110V up to 48000 BTUH recommended	☐ X87-711
	Blue Diamond MegaBlue Advanced Condensate Pump w Reservoir Sensor	☐ X87-835
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Sauermann Condensate Pump	☐ SI30-230
	Blue Diamond MicroBlue Mini Condensate Pump 110208230V up to 18000 BTUH	☐ X86-003
Control Interface	kumo station for the Comfort app	☐ PAC-WHS01HC-E
	Wireless Interface Adapter for the Comfort app	☐ PAC-USWHS002-WF-2
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Airzone Wired Lite Controller White	☐ AZZBSLITECB
	IT Extender for kumo station	☐ PAC-WHS01IE-E
	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	Operation and Error Status Output Adapter	☐ PAC-SF40RM-E
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	Airzone Wired Lite Controller Black	☐ AZZBSLITECN
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
Control Wire	202PR 1PR shielded 1PR plenum wire for Airzone 100 ft reel	☐ CW2042S2-100
	202PR shielded 1PR plenum wire for Airzone 500 ft reel	☐ CW2042S2-500
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
	30A600VUL fits 2 X 4 utility box - White	☐ TAZ-MS303W
Filter Box	Filter Box with 1" thick pleated MERV 13 Filter	☐ FBL1-3
Lineset	50 x 1/4 x 50 1/2 Lineset Twin-Tube Insulation	☐ MLS141212T-50
	30 x 1/4 x 30 1/2 Lineset Twin-Tube Insulation	☐ MLS141212T-30
	15 x 1/4 x 15 1/2 Lineset Twin-Tube Insulation	☐ MLS141212T-15
	100 x 1/4 x 100 1/2 Lineset Twin-Tube Insulation	☐ MLS141212T-100
	65 x 1/4 x 65 1/2 Lineset Twin-Tube Insulation	☐ MLS141212T-65
Remote Sensor	Wireless temperature and humidity sensor for the Comfort app	☐ PAC-USWHS003-TH-1
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	☐ PAC-USSEN002-FM-1
	Wall Mount Remote Temperature Sensor	☐ PAC-SE41TS-E
Terminal Signal Adapter	5-Pin Wiring Harness	☐ PAC-725AD
	3-Pin Wiring Harness	☐ PAC-715AD
	Backup Heat Relay Kit Adapter for CN24 or CN152 Connector	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Simple MA Remote Controller	☐ PAC-YT53CRAU-J
	Touch MA Wired Remote Controller	☐ PAR-CT01MAU-SB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Deluxe Wired MA Remote Controller	☐ PAR-42MAAUB
Wireless Remote Controller	Wireless Universal Signal Receiver (for PAR-SL101A-E)	☐ PAR-SA9CA-E
	RedLINK Wireless Remote Controller	☐ MHK2
	Universal Wireless Receiver for PAR-FL32MA-E	☐ PAR-FA32MA-W
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
Notes ¹ Requires MAC-3341F-E Interface to connect MA controller ¹ Unable to use with Wireless Handheld Remote Controller		


OUTDOOR UNIT ACCESSORIES: SUZ-AA18NLHZ

Air Outlet Guide	Air Outlet Guide	☐	MAC-890SG-E
Control/Service Tool	Maintenance Tool Interface	☐	PAC-USCMS-MN-1
	M- & P-Series Maintenance Tool Cable Set	☐	M21EC0397
Drain Socket	Drain Socket	☐	MAC-871DS
Hail Guards	Hail Guard	☐	HG-A7
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	☐	SW144-50
	14 Gauge 4 wire MiniSplit Cable50 ft roll	☐	S144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	☐	S144-250
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	☐	SW144-250
Mounting Pad	Condensing Unit Mounting Pad 16 x 36 x 3	☐	ULTRILITE1
Muffler	Muffler	☐	MAC-002MF-E
Snow/Rain Diverter	SnowRain Diverter	☐	SRD-3
Stand	18 Single Fan Stand	☐	QSMS1801M
	Condenser Wall Bracket	☐	QSWB2000M-1
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	☐	DSD-400P
	24 Single Fan Stand	☐	QSMS2401M
	Outdoor Unit Stand 12 High	☐	QSMS1201M
	Condenser Wall Bracket - Stainless Steel Finish	☐	QSWBSS
Notes			

INDOOR UNIT DIMENSIONS: SEZ-AD18NL

Model	A	B	C	D	E	F	G	H	J	K	L	M	Gas pipe	Liquid pipe
SEZ-AD09NL	700 (27-39)	752 (23-58)	798 (31-71)	660 (26)	600 (23-58)	600 (26)	500 (19-11)	500 (19-11)	16 (33-11)	839 (33-11)	790 (31-18)		ø9.52 (3/8)	
SEZ-AD12NL	900 (35-71)	952 (37-12)	998 (39-51)	860 (33-7/8)	800 (31-12)	800 (33-7/8)	700 (27-9)	700 (27-9)	20 (40-28)	1039 (40-28)	990 (39)		ø6.35 (1/4)	
SEZ-AD15NL	1100 (43-57)	1152 (45-38)	1198 (47-31)	1060 (41-3/4)	1000 (41-3/4)	1000 (41-3/4)	900 (35-7/16)	900 (35-7/16)	24 (48-25)	1239 (48-25)	1180 (46-7/8)		ø12.7 (1/2)	
SEZ-AD18NL	1300 (50-59)	1352 (52-40)	1398 (54-33)	1260 (50-1/2)	1200 (50-1/2)	1200 (50-1/2)	1100 (44-1/2)	1100 (44-1/2)	30 (60-31)	1439 (60-31)	1380 (58-1/8)		ø15.88 (3/2)	

Unit:mm(in.)




Note 1 Use M10 screw for the suspension bolt (old supply).
 2.Keep the service space for the maintenance at the bottom.
 3.This chart indicates for SZ-AD15NL model, which have 3 fans.
 SZ-AD09 12NL models have 2 fans.
 SZ-AD18NL model have 4 fans.
 4.In case of the inlet duct is used, remove the air filter (supply with the unit), then install the filter (old supply) at suction side.

\$ w t V x ~ ? ; q t K {

	^ R	ISSUED	DATE	EXTERNAL DIMENSION	ORDER NO W 1694070H	REV 1/2
	DIMENSIONS ARE IN MILLIMETERS		REVISED 2024-06-13	SEZ-AD09 12 15 18NL		

OUTDOOR UNIT DIMENSIONS: SUZ-AA18NLHZ

REQUIRED SPACE



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com

METUS_2026-07_PROPIN

